

## Technical Data Sheet

### Mintepox® YMR 821

**Description** reactively diluted bisphenol-A-epoxy resin

**Properties and Fields of Application** Mintepox® YMR 821 is a monofunctionally reactively diluted liquid epoxy resin based on bisphenol A. Mintepox® YMR 821 is a universally applicable epoxy resin blend, which is used for the formulation of pigmented coatings, mortars, and the like. Mintepox® YMR 821 has only a low tendency for crystallization on extended storage.

	<i>Property</i>	<i>lower limit</i>	<i>upper limit</i>	<i>Measuring Unit</i>	<i>Method of Determination</i>
<b>Specification</b>	Viscosity at 23 °C	1,100	1,500	mPas	ISO 3219
	Epoxy Equiv. Weight	180	200	g/eq.	DIN EN 1877-1
	FTIR comparison	PASS			
	Gardner Colour Index		2		ISO 4630-2
	Density at 23 °C	1.11	1.13	g/mL	ISO 2811-2
<b>Characteristic Data</b>		Value			
	Solid Content		100	w.-%	calculated

**Storage** At room temperature, the shelf life in original, unopened containers is at least 12 months.

**Occupational Safety** When processing epoxy resins and hardeners, the usual precautionary and hygiene measures for handling chemicals as well as the applicable official occupational safety and environmental protection regulations must be observed. Particular attention must be paid to skin and eye protection and the selection of suitable protective gloves. Detailed information on hazards, labeling, occupational safety and environmental protection can be found in the product safety data sheet.

The information given in this technical data sheet is based on carefully executed tests and is intended to give orientation to the user. However, it is non-binding as we cannot take over any liability, also related to possible protective rights of third parties, due to the variety of treatments and applications.